

Firestone

SRG/SRG LD E-3 E3/L3 L-3

**SUPER ROCK GRIP / SUPER ROCK
GRIP LOADER DOZER**



The **SUPER ROCK GRIP** bias ply tire offers a heavy duty non-directional tread design. It features exceptional traction and resistance to cutting and chipping in loader/dozer applications, as well as heat resistance in earthmover and grader service.

SPECIALIZED FEATURES

- **Non-directional rock tread pattern provides excellent flotation**
- **Long lasting cut and impact resistant compounding**
- **Widebase sizes offer wide cross section and tread**

SRG/SRG LD E-3,E3/L3,L-3

SUPER ROCK GRIP / SUPER ROCK GRIP LOADER DOZER



CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT.	OTD (32ND)	OVERALL DIAMETER	OVERALL WIDTH
SMALL TUBELESS	16.00-25	28		E-3	413518	460	36	58.8	17.2
	17.5-25	12	LD CRC	L-3	425537	220	32	53.4	18.0
	17.5-25	16	LD	L-3	425554	240	32	53.4	18.0
	17.5-25	20	LD	L-3	425571	330	32	53.4	18.0
	18.00-25	32		E-3	411973	700	40	63.7	20.0
	20.5-25	16	LD	E3/L3	408476	350	35	58.8	21.2
	20.5-25	20	LD	E3/L3	414646	380	35	59.0	21.1
	20.5-25	24	LD	E3/L3	423181	410	35	59.0	21.1
	23.5-25	16	LD	E3/L3	400556	510	39	63.9	24.2
	23.5-25	20	LD	E3/L3	400610	550	39	63.9	24.2
LARGE TUBELESS	26.5-25	20	LD	E3/L3	400629	760	44	69.2	26.6
	26.5-25	26	LD	E3/L3	401757	790	44	69.2	26.6
	29.5-25	28	LD	E3/L3	414638	1,060	48	74.0	30.8
	29.5-29	28		E-3	401889	1,180	48	78.0	30.8
	29.5-29	34		E-3	401625	1,220	48	78.0	30.8
	29.5-29	40	LD	L-3	416916	1,380	48	78.0	30.8
	33.25-29 +	32		E-3	280138	1,590	57	82.3	33.9
	33.25-35	38		E-3	410241	1,870	53	89.7	33.7
	37.25-35 +	36		E-3	413461	2,240	62	94.7	37.9
	37.5-33	42		E-3	401501	2,220	58	93.3	38.2
GIANT TUBELESS	37.5-39 +	52		E-3	412546	2,780	60	99.5	38.0
	18.00-49	32		E-3	401560	1,100	34	87.9	20.1

LD: Loader/Dozer

BRIDGESTONE
OFF THE ROAD TIRES